

## Notes:

- Maximum Electric Current: 

|     |    |    |    |    |
|-----|----|----|----|----|
| AWG | 22 | 20 | 18 | 16 |
| AMP | 3  | 4  | 7  | 10 |
- Maximum Electrical Rating: 105° 600 Volts Max.
- Insulation Material: Vinyl
- Insulation Color: Red
- Terminal Material: Brass
- Wire Range: 22-16 AWG (0.5-1.5mm<sup>2</sup>)
- Terminal Surface Treatment: Tin Plated
- Nema Tab: 0.032" x 0.110" (0.8mm x 2.80mm)
- Double Crimp
- Terminal Thickness: 0.30mm

### Standard (Metric)

0.75" (19mm)  
 0.41" (10.5mm)  
 0.26" (6.5mm)  
 0.13" (3.2mm)  
 0.07" (1.7mm)  
 0.16" (4mm)

### Tolerances

(Unless Otherwise Specified)

0 > 6mm ± 0.20  
 6 > 18mm ± 0.30  
 18 > 30mm ± 0.40  
 30 > 75mm ± 0.50

| CATEGORY | Female Vinyl Insulated<br>Double Crimp Disconnects | SCALE | 4/1  |
|----------|--|-------|------|
| PART #   | FDD1-110(8)  | SHEET | 1-2  |
| MATERIAL | Tin-Plated Brass                                   | PAGE  | 10F2 |

