

**Notes:**

- Maximum Electric Current: 

|     |    |    |  |
|-----|----|----|--|
| AWG | 16 | 14 |  |
| AMP | 10 | 13 |  |
- Maximum Electric Rating: 105°C 300 Volts Max
- Insulation Material: Nylon
- Insulation Color: Blue
- Terminal Material: Brass
- Wire Range: 16-14 AWG (1.5-2.5mm<sup>2</sup>)
- Terminal Surface Treatment: Tin Plated
- Terminal Thickness: 0.35mm
- Nema Tab: 0.032" x 0.205" (0.8mm x 5.20mm)

**Standard (Metric)**

- 0.77" (19.5mm)
- 0.43" (11mm)
- 0.23" (5.8mm)
- 0.22" (5.7mm)
- 0.09" (2.3mm)
- 0.18" (4.5mm)

**Tolerances**

(Unless Otherwise Specified)

- 0 > 6mm ± 0.20
- 6 > 18mm ± 0.30
- 18 > 30mm ± 0.40
- 30 > 75mm ± 0.50

|                 |                          |              |      |
|-----------------|--------------------------|--------------|------|
| <b>CATEGORY</b> | Female Quick Disconnects | <b>SCALE</b> | 4/1  |
| <b>PART #</b>   | FDNY2-205(8)             | <b>SHEET</b> | 1-1  |
| <b>MATERIAL</b> | Tin-Plated Brass         | <b>PAGE</b>  | 10F2 |

