

Notes:

- Maximum Electric Current:

| | | | |
|-----|----|----|----|
| AWG | 22 | 20 | 18 |
| AMP | 3 | 4 | 7 |
- Terminal Material: Brass
- Wire Range: 22-18 AWG (0.5-0.75mm²)
- Terminal Surface Treatment: Tin Plated
- Nema Tab: 0.032" x 0.187" (0.8mm x 4.75mm)

Standard (Metric)

- 0.44" (11.3mm)
- 0.24" (6.2mm)
- 0.23" (5.8mm)
- 0.20" (5mm)
- 0.06" (1.4mm)
- 0.22" (5.5mm)
- 0.14" (3.5mm)
- 0.07" (1.7mm)
- 0.11" (2.7mm)

Tolerances

(Unless Otherwise Specified)

- 0 > 6mm ± 0.20
- 6 > 18mm ± 0.30
- 18 > 30mm ± 0.40
- 30 > 75mm ± 0.50

| | | | |
|-----------------|--------------------------------------|--------------|------|
| CATEGORY | Non Insulated Flag Quick Disconnects | SCALE | 5/1 |
| PART # | FLDNB1-187(8) | SHEET | 1-0 |
| MATERIAL | Tin-Plated Brass | PAGE | 10F1 |

