

Notes:

1. Maximum Electric Current:

| | | | | |
|-----|----|----|----|----|
| AWG | 22 | 20 | 18 | 16 |
| AMP | 3 | 4 | 7 | 10 |
2. Terminal Material: Brass
3. Insulation Material: Nylon
4. Insulation Color: Red
5. Maximum Electrical Rating: 105° 600 Volts Max.
6. Wire Range: 22-16 AWG (0.5-1.5mm²)
7. Terminal Surface Treatment: Tin Plated
8. Terminal Thickness: 0.40mm

Standard (Metric)

- 0.99" (25.2mm)
- 0.43" (11mm)
- 0.28" (7mm)
- 0.15" (3.9mm)
- 0.07" (1.7mm)
- 0.16" (4mm)

Tolerances

(Unless Otherwise Specified)

- 0 > 6mm ± 0.20
- 6 > 18mm ± 0.30
- 18 > 30mm ± 0.40
- 30 > 75mm ± 0.50

| | | | |
|-----------------|---|--------------|------|
| CATEGORY | Nylon Insulated Female Bullet Connector | SCALE | 4/1 |
| PART # | FRFNY1-156 | SHEET | 1-1 |
| MATERIAL | Tin-Plated Brass | PAGE | 10F2 |

