

## Notes:

- Maximum Electric Current: 

|     |    |    |    |    |
|-----|----|----|----|----|
| AWG | 22 | 20 | 18 | 16 |
| AMP | 3  | 4  | 7  | 10 |
- Terminal Material: Brass
- Insulation Material: Vinyl
- Insulation Color: Red
- Maximum Electrical Rating: 75° 600 Volts Max.
- Wire Range: 22-16 AWG (0.5-1.5mm<sup>2</sup>)
- Terminal Surface Treatment: Tin Plated
- Terminal Thickness: 0.40mm

### Standard (Metric)

0.91" (23mm)  
 0.41" (10.5mm)  
 0.28" (7mm)  
 0.15" (3.9mm)  
 0.07" (1.7mm)  
 0.16" (4mm)

### Tolerances

(Unless Otherwise Specified)

0 > 6mm ± 0.20  
 6 > 18mm ± 0.30  
 18 > 30mm ± 0.40  
 30 > 75mm ± 0.50

|                 |  |              |      |
|-----------------|--|--------------|------|
| <b>CATEGORY</b> | Vinyl Fully Insulated<br>Female Bullet Connector | <b>SCALE</b> | 4/1  |
| <b>PART #</b>   | FRV1-156   | <b>SHEET</b> | 1-1  |
| <b>MATERIAL</b> | Tin-Plated Brass                                 | <b>PAGE</b>  | 10F2 |



# MIROMAR

