

Notes:

1. Maximum Electric Current:

| | | | | |
|-----|----|----|----|----|
| AWG | 22 | 20 | 18 | 16 |
| AMP | 9 | 12 | 17 | 30 |
2. Maximum Electric Rating: 105°C 600 Volts Max
3. Insulation Material: Vinyl
4. Insulation Color: Red
5. Terminal Material: Copper
6. Wire Range: 22-16 AWG (0.5-1.5mm²)
7. Terminal Surface Treatment: Tin Plated
8. Terminal Thickness: 0.75mm
9. Double Crimp

Standard (Metric)

- 0.76" (19.3mm)
- 0.41" (10.5mm)
- 0.35" (9mm)
- 0.07" (1.9mm)
- 0.07" (1.7mm)
- 0.17" (4.2mm)

Tolerances

(Unless Otherwise Specified)

- 0 > 6mm ± 0.20
- 6 > 18mm ± 0.30
- 18 > 30mm ± 0.40
- 30 > 75mm ± 0.50

| | | | |
|-----------------|--|--------------|------|
| CATEGORY | Vinyl Insulated Double Crimp Pin Terminals | SCALE | 4/1 |
| PART # | PTD1-9 | SHEET | 1-4 |
| MATERIAL | Tin-Plated Copper | PAGE | 10F1 |

